



Direct Hydraulic Snow Wing

WITH DIRECTLINK™
TRUCK MOUNTED



- 9, 10, 11, and 12 ft. Cutting Edge Lengths
- 3.5" Diameter Double-Acting Hydraulic Cylinders
- 1-3/4" Wing Hinge Bolt
- Trip Edge or Trip Moldboard Available
- Flotation Front Saddle with DirectLink™ Slide
- AASHO & Carbide Punch Available
- Two (2) Cylinder Control for Precise Positioning
- Heavy-Duty Construction Throughout
- Hydraulic Power Front Sideshift Available
- Shown with Optional Nitrogen-Accumulated Hydraulic Push Bar Extension



**Model
TDL-10**



Specifications

MODEL	TDL-9	TDL-10	TDL-11
Overall length	9'6"	10'6"	11'6"
Overall height, front	30"		
Overall height, rear	30"		
Moldboard thickness	10 gauge hi-tensile steel, A607-50		
Cutting Edge (AASHO Punched)	5/8" x 6" x 9ft	1/2" x 6" x 10ft	1/2" x 6" x 11ft
Push Bar	One (1) adjustable spring-cushioned – Hydraulic extension optional		
Clearing width	60" - 90"	70" - 100"	80" - 110"
Front lift height	18"		
Rear lift height	96"	102"	108"
Weight, wing only	580 lb	640 lb	700 lb
Weight, wing & mtgs	1550 lb	1610 lb	1670 lb

Valves required: Two (2) double-acting hydraulic control valves.

Frame required: Factory integral frame extension or equal, minimum 18".

Options available: Trip edge or trip moldboard, nitrogen-accumulated hydraulic push bar extension, hydraulic sideshift. Mounting positions available: front, mid, rear and scraper.

YOUR DEALER IS:

The policy and promise of Little Falls Machine, Inc. is continuing product improvement. Design change and structural alterations may occur without prior notice. Such changes will not sacrifice quality or product integrity.

Falls®, DirectLink™, and IceBreaker™ are trademarks of Little Falls Machine, Inc. Little Falls Machine, Inc. is an equal opportunity employer.

0106-500-SP



LITTLE FALLS MACHINE, INC.

300 Lindbergh Drive South
 Little Falls, MN 56345
 Phone 800-772-PLOW
 (320) 632-9266 Fax (320) 632-3484
www.fallsplovs.com